# Multi Kleen Degreaser & Covid-19 Killer Concentrate LEFT PILLAR PTY LTD TA'S SHIELD CHEMICALS

Chemwatch: 5471-84

Version No: 4.1 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements Chemwatch Hazard Alert Code: 3

Issue Date: **19/07/2021** Print Date: **26/11/2021** S.GHS.AUS.EN

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Multi Kleen Degreaser & Covid-19 Killer Concentrate	
Chemical Name	lot Applicable	
Synonyms	19	
Proper shipping name	CORROSIVE LIQUID, N.O.S. (contains benzalkonium chloride and didecyldimethylammonium chloride)	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Multi Kleen Degreaser & Covid-19 Killer Concentrate is an industrial hard surface cleaner degreaser that when diluted with 9 parts water is a Hospital grade Disinfectant Dirty Conditions, formulated to be effective against germs, bacteria and the SARS-CoV-2 COVID19 virus.

#### Details of the supplier of the safety data sheet

Registered company name	LEFT PILLAR PTY LTD TA'S SHIELD CHEMICALS	
Address	Unit 3/20 Badgally Rd, Campbelltown, Sydney NSW, 2560 Australia	
Telephone	+61 1300 519 074	
Fax	Not Available	
Website	www.krystalshield.com.au	
Email	info@krystalshield.com.au	

#### Emergency telephone number

- <b>J</b>		
Association / Organisation	LEFT PILLAR PTY LTD TA'S SHIELD CHEMICALS	
Emergency telephone numbers	+61 1300 519 074	
Other emergency telephone numbers	Not Available	

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Poisons Schedule	S5	
Classification <sup>[1]</sup>	Corrosive to Metals Category 1, Skin Corrosion/Irritation Category 1B, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Sensitisation (Respiratory) Category 1, Hazardous to the Aquatic Environment Acute Hazard Category 2	
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

#### Label elements

Signal word Danger

#### Hazard statement(s)

H290	Vay be corrosive to metals.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H401	Toxic to aquatic life.	

#### Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.

P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P284	n case of inadequate ventilation] wear respiratory protection.	
P234	Keep only in original packaging.	
P273	Avoid release to the environment.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

#### Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P363	Wash contaminated clothing before reuse.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P390	Absorb spillage to prevent material damage.	

#### Precautionary statement(s) Storage

Store locked up.

#### Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### SECTION 3 Composition / information on ingredients

P405

P501

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
8001-54-5	1-10	benzalkonium chloride
111-76-2	1-10	ethylene glycol monobutyl ether
7173-51-5	1-5	didecyldimethylammonium chloride
6834-92-0	1-5	sodium metasilicate, anhydrous
57-55-6	1-5	propylene glycol
27176-87-0	1-5	dodecylbenzenesulfonic acid
Not Available	balance	Ingredients determined not to be hazardous
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

#### **SECTION 4 First aid measures**

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>Quickly remove all contaminated clothing, including footwear.</li> <li>Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>Transport to hospital, or doctor.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> </ul>

	This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For exposures to quaternary ammonium compounds;

- For ingestion of concentrated solutions (10% or higher): Swallow promptly a large quantity of milk, egg whites / gelatin solution. If not readily available, a slurry of activated charcoal may be useful. Avoid alcohol. Because of probable mucosal damage omit gastric lavage and emetic drugs.
- For dilute solutions (2% or less): If little or no emesis appears spontaneously, administer syrup of Ipecac or perform gastric lavage.
- If hypotension becomes severe, institute measures against circulatory shock.
- If respiration laboured, administer oxygen and support breathing mechanically. Oropharyngeal airway may be inserted in absence of gag reflex. Epiglottic or laryngeal edema may necessitate a tracheotomy.
- Persistent convulsions may be controlled by cautious intravenous injection of diazepam or short-acting barbiturate drugs. [Gosselin et al, Clinical Toxicology of Commercial Products]

#### **SECTION 5 Firefighting measures**

#### Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

Fire Incompatibility	None known.
for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>Do not approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered to be a significant fire risk.</li> <li>Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>May emit corrosive, poisonous fumes. May emit acrid smoke.</li> <li>carbon dioxide (CO2)</li> <li>hydrogen chloride</li> <li>phosgene</li> <li>nitrogen oxides (NOx)</li> <li>other pyrolysis products typical of burning organic material.</li> </ul>
HAZCHEM	2X

#### **SECTION 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>Check regularly for spills and leaks.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>

Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Consider evacuation (or protect in place).</li> <li>Stop leak if safe to do so.</li> <li>Contain spill with sand, earth or vermiculite.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>
--------------	--

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

Precautions for safe handling	
Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Avoid contact with moisture.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with scap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

#### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>DO NOT use aluminium or galvanised containers</li> <li>Check regularly for spills and leaks</li> <li>Lined metal can, lined metal pail/ can.</li> <li>Plastic pail.</li> <li>Polyliner drum.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</li> <li>Removable head packaging;</li> <li>Cans with friction closures and</li> <li>low pressure tubes and cartridges may be used.</li> <li>Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> </ul>
Storage incompatibility	<ul> <li>Quaternary ammonium cations are unreactive toward even strong electrophiles, oxidants, and acids. They also are stable toward most nucleophiles. The latter is indicated by the stability of the hydroxide salts such as tetramethylammonium hydroxide and tetrabutylammonium hydroxide.</li> <li>Quaternary ammonium compounds are deactivated by anionic detergents (including common soaps).</li> <li>With exceptionally strong bases, quat cations degrade. They undergo Sommelet–Hauser rearrangement and Stevens rearrangement, as well as dealkylation under harsh conditions. Quaternary ammonium cations containing N–C–C–H units can also undergo the Hofmann elimination and Emde degradation.</li> <li>Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.</li> <li>Avoid strong bases.</li> <li>Avoid strong bases.</li> <li>Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates.</li> </ul>

## **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

#### Occupational Exposure Limits (OEL)

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	20 ppm / 96.9 mg/m3	242 mg/m3 / 50 ppm	Not Available	Not Available

Version No: 4.1

#### Multi Kleen Degreaser & Covid-19 Killer Concentrate

Source	Ingredient	Material name	•	TWA	STEL	Peak	Notes	
Australia Exposure Standards	propylene glycol	Propane-1,2-diol total: (vapour & particulates)		150 ppm / 474 mg/m3	Not Available	Not Available	Not Available	
Australia Exposure Standards	propylene glycol	Propane-1,2-d	iol: particulates only	10 mg/m3	Not Available	Not Available	Not Available	
Emergency Limits								
Ingredient	TEEL-1		TEEL-2		TEEL-3			
benzalkonium chloride	0.91 mg/m3		10 mg/m3		60 mg/m3			
ethylene glycol monobutyl ether	60 ppm		120 ppm		700 ppm			
didecyldimethylammonium chloride	0.82 mg/m3		9 mg/m3		17 mg/m3			
sodium metasilicate, anhydrous	3.8 mg/m3		42 mg/m3		250 mg/m3	3		
propylene glycol	30 mg/m3		1,300 mg/m3		7,900 mg/i	m3		
dodecylbenzenesulfonic acid	2 mg/m3		21 mg/m3		130 mg/m3	3		
Ingredient	Original IDLH			Revised IDLH				
benzalkonium chloride	Not Available			Not Available	Not Available			
ethylene glycol monobutyl ether	700 ppm		Not Available	Not Available				
didecyldimethylammonium chloride	Not Available		Not Available	Not Available				
sodium metasilicate, anhydrous	Not Available		Not Available					
propylene glycol	Not Available		Not Available					
dodecylbenzenesulfonic acid	Not Available		Not Available					
Occupational Exposure Banding	I							
Ingredient	Occupational Exposur	e Band Rating		Occupational	Exposure Band L	.imit		
benzalkonium chloride	E			≤ 0.01 mg/m³				
didecyldimethylammonium chloride	E		≤ 0.01 mg/m³					
sodium metasilicate, anhydrous	E			≤ 0.01 mg/m³				
dodecylbenzenesulfonic acid	E	E						
Notes:	Occupational exposure a adverse health outcome range of exposure conce	s associated with exp	posure. The output of th	is process is an occup				
xposure controls								
	Engineering controls are be highly effective in pro The basic types of engir Process controls which i Enclosure and/or isolatic	otecting workers and neering controls are: involve changing the	will typically be indepen way a job activity or pro	dent of worker interact	ions to provide this e the risk.	high level of protec	tion.	

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape"

	velocities which, in turn, determine the "capture velocities" of	taminant.	
	Type of Contaminant:		Air Speed:
	solvent, vapours, degreasing etc., evaporating from tank (in	0.25-0.5 m/s (50-100 f/min.)	
Appropriate engineering controls	drift plating agid fumor, pickling (released at low valacity into zone of active generation)		
	direct spray, spray painting in shallow booths, drum filling, generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	
	grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	
	Within each range the appropriate value depends on:		
	Lower end of the range	Upper end of the range	
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
	Or laste and its act laws are direction.	2. High production because	

 3: Intermittent, low production.
 3: High production, heavy use

 4: Large hood or large air mass in motion
 4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations,

	producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
Personal protection	
Eye and face protection	<ul> <li>Chemical goggles.</li> <li>Full face shield may be required for supplementary but never for primary protection of eyes.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear schemical protective gloves, e.g. PVC.</li> <li>Wear schemical protective gloves, e.g. Rubber</li> <li>When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.</li> <li>NDTE:</li> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> <li>The saterial may produce skin sensitisation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact three with chemical is a preparation of several substances, the resistance of the glove and has to be observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</li> <li>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:         <ul> <li>if requere, and duration of contact.</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> </ul> </li> <li>Select gloves steted to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</li> <li>When prolonged or frequently repeated contact may occur, a glow with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1 or national equivalent).</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>Contaminated glove</li></ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower.</li> </ul>

#### Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the *computer*generated selection: Multi Kleen Degreaser & Covid-19 Killer Concentrate

Material	СРІ
BUTYL	С
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С

#### **Respiratory protection**

Type ABK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum	Half-Face	Full-Face	Powered Air
Protection Factor	Respirator	Respirator	Respirator
up to 10 x ES	ABK-AUS P2	-	ABK-PAPR-AUS / Class 1 P2

NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PE	С
PE/EVAL/PE	С
PVA	С
PVC	С
SARANEX-23	С
SARANEX-23 2-PLY	С
TEFLON	С
VITON	С
VITON/CHLOROBUTYL	С

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### **SECTION 9** Physical and chemical properties

#### Information on basic physical and chemical properties

 
 up to 50 x ES
 ABK-AUS / Class 1 P2

 up to 100 x ES
 ABK-2 P2
 ABK-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

76ak-p()

Appearance	Green liquid with Eucalyptus odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Fliysical state		,	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

Information on toxicological effects

Inhaled

Ethylene glycol monobutyl ether can destroy the blood cells with long term exposure. It also causes eye, nose and throat discomfort. Higher doses can cause blood in the urine.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Concentrated solutions of many cationics may cause corrosive damage to mucous membranes and the oesophagus. Nausea and vomiting (sometimes bloody) may follow ingestion. Severe acute exposure to ethylene glycol monobutyl ether, by ingestion, may cause kidney damage and blood in the urine, and is potentially fatal.		
Skin Contact	The material can produce chemical burns following direct contact with the skin. Cationic surfactants cause skin irritation, and, in high concentrations, caustic burns. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Ethylene glycol monobutyl ether penetrates the skin easily and will cause more harm on skin contact than through inhalation. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.		
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Irritation of the eyes may produce a heavy secretion of tears (lachrymation). Many cationic surfactants are very irritating to the eyes at low concentration. Concentrated solutions can cause severe burns with permanent clouding. Ethylene glycol monobutyl ether may cause pain, redness and damage to the eyes.		
Chronic	Skin contact with the material is more likely to cause a sen Prolonged or repeated skin contact may cause degreasing	nd may cause some concern following repeated or long-term occupational exposure.	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
Multi Kleen Degreaser & Covid-19 Killer Concentrate	Not Available	Not Available	
benzalkonium chloride	Dermal (rabbit) LD50: 1560 mg/kg <sup>[2]</sup> Oral(Rat) LD50; 240 mg/kg <sup>[2]</sup>	Eye (human): 0.05 mg SEVERE Eye (rabbit): 1mg/24h SEVERE	
		Skin (human): 0.15 mg/72h mild	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (guinea pig) LD50: 210 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg SEVERE	
ethylene glycol monobutyl	Inhalation(Rat) LC50; 2.21 mg/l4h <sup>[2]</sup>	Eye (rabbit): 100 mg/24h-moderate	
ether	Oral(Rat) LD50; 300 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin (rabbit): 500 mg, open; mild Skin: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin: no adverse effect observed (initiality). <sup>[1]</sup>	
didecyldimethylammonium			
chloride	dermal (rat) LD50: >1000 mg/kg <sup>[1]</sup>	Skin (rabbit): 500 mg SEVERE	
	Oral(Rat) LD50; 84 mg/kg <sup>[2]</sup>		
	ΤΟΧΙCΙΤΥ	IRRITATION	
sodium metasilicate,	dermal (rat) LD50: >5000 mg/kg <sup>[1]</sup>	Skin (human): 250 mg/24h SEVERE	
anhydrous	Inhalation(Rat) LC50; >2.06 mg/l4h <sup>[1]</sup>	Skin (rabbit): 250 mg/24h SEVERE	
	Oral(Rat) LD50; 1153 mg/kg <sup>[2]</sup>		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - mild	
	Inhalation(Rat) LC50; >44.9 mg/L4h <sup>[2]</sup>	Eye (rabbit): 500 mg/24h - mild	
propylene glycol	Oral(Rat) LD50; 20000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
		Skin(human):104 mg/3d Intermit Mod	
		Skin(human):500 mg/7days mild	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >212 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	
dodecylbenzenesulfonic acid	Inhalation(Rat) LC50; 0.31 mg/L4h <sup>[1]</sup>	Skin: adverse effect observed (corrosive) <sup>[1]</sup>	
	Oral(Rat) LD50; 500-2000 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	

BENZALKONIUM CHLORIDE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins. Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. Alkyldimethylbenzylammonium chlorides are in the list of dangerous substances of council directive, classified as "narmful in contact with skin and on ingestion", and "corrosive and very toxic to aquatic organisms". It can cause dose dependent skin and eye irritation with possible deterioration of vision,
ETHYLENE GLYCOL MONOBUTYL ETHER	<ul> <li>NOTE: Changes In kidney, liver, platen and lungs are observed in animals exposed to high concentrations of this substance by all routes. ** ASCC (N2): SDS</li> <li>The material may produce some initiation to the eye causing pronounced inflammation. Repeated or prolonged exposure to inflams may produce computerionity.</li> <li>For othylene dyl-col monology, lethers and their acetates (EGMAEs):</li> <li>Typical members of this category are driven dyl-or groyome other (EGPE), ethylene dyl-col budy other (EGBE) and ethylene dyl-col hexyl ether (EGPE) and their acetates.</li> <li>Method the transmitter metholelies, 1-ther, rapid comments may for monology of the some conclusion.</li> <li>Acute Toxicity: Col LDSG values in earls for al category on members mays from 739 (EGHE) to 388 mays by CGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalisticit y sudies were conducted for these chemicals in rate highest vapour concentrations practically achievable. Values mays from 12:0:9 EGHE, 10:0:00 Mg/b to 4000 (EGHE), LOSO 4000 (EGDE), and EGHE and CGHE in 10:00 Mg/b to 10:0</li></ul>
	appears to be rare and usually seen after swallowing higher doses of ethylene glycol. In summary, acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

	Gastrointestinal effects: Common early acute effects of swallowing ethylene glycol include nausea, vomiting with or without blood, heartburn and abdominal cramping and pain. One patient showed intermittent diarrhea and pain, and after surgery, deposition of oxalate crystals was shown to have occurred. Musculoskeletal effects: Reported musculoskeletal effects in cases of acute ethylene glycol poisoning include diffuse muscle tenderness and pain, associated with high levels of creatinine in the blood, and jerks and contractions associated with low calcium. Liver effects: Autopsies carried out on people who died following acute ethylene glycol poisoning showed deposition of calcium oxalate in the liver as well as hydropic and fatty degeneration and cell death (necrosis) of the liver. Kidney effects: Adverse kidney effects are seen during the third stage of ethylene glycol poisoning, 2-3 days after acute exposure. Calcium oxalate crystals are deposited in the tubules and are seen in the urine. There may also be degeneration and death of tubule cells, and inflammation of the tubule interstitium. If untreated, the degree of kidney damage progresses and leads to blood and protein in the urine, decreased kidney function, reduction in urine output and ultimately, kidney failure. With adequate supportive therapy, kidney function can return to normal or near normal. Metabolic effects: Metabolic changes can occur within 12 hours of exposure to ethylene glycol. There may be metabolic acidosis, caused by accumulation of glycolic acid in the blood and therefore a reduction in blood pH. The anion gap is increased, due to increased unmeasured anions (mainly glycolate). Effects on the nervous system: Adverse reactions involving the nervous system are among the first symptoms to appear in humans after ethylene glycol is swallowed. These early effects are also the only symptoms caused by unmetabolised ethylene glycol. Together with metabolic effects (see above), they occur from 0.5-12 hours after exposure and are considered to be
DIDECYLDIMETHYLAMMONIUM CHLORIDE	Control total, Teor Industry Teor Industry Status and Status and Consistential (Equation) in Equation. Somolence recorded. There is no data that exists regarding the health effects of cationic dialkyldimethylammonium (DADMA) salts, but they are expected to have similar properties to alkyltrimethylammonium (ATMA) salts, although they are generally less irritating than the corresponding ATMA salts Fatty Nitrogen-Derived Cationics (FND Cationics) have minimal to moderate acute toxicity but may be acutely lethal at very high doses. Repeated exposure also is associated with low toxicity. They are unlikely to cause mutation or affect reproduction, cause birth defects or development of the unborn. For alkyltrimethylammonium chloride (ATMAC) Most undiluted cationic surfactants satisfy the criteria for classification as Corrosive with R34 in addition to the acute toxicity. According to Centre Europeen des Agents de Surface et de leurs Intermediares Organiques (CESIO), CB-18 alkyltrimethylammonium chloride (ATMAC) (and the criteria for classification as Corrosive). CB-18 alkyltrimethylammonium chloride (ATMAC) is classified as Harmful (Xn) with the risk phrases R22 (Harmful 1 if swallowed), CB-18 alkyltrimethylammonium satts is somewhat higher than the toxicity of anionic and nonionic surfactants. This may be due to the strongly irritating for alkyltrimethylammonium satts is somewhat higher than the toxicity of anionic and nonionic surfactants. This may be due to the strongly irritating effect which actionic surfactants have on the mucous membrane of the gastrointestinal trat. Cationic surfactants are generally about 10 times more toxic when given through a vein, compared to being give through the eke. Many proteins in the skin are considerably more resistant to the denuuring effects of cationic surfactants compared to hese of anionic autonomotic surfactants. This may be due to the strongly irritating effect which cationic surfactants on the reversible denaturing effect of sodium dodey! suffat, the adverse effects of som
PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most. Poisonings are usually due to injection through a vein or accidental swallowing of large amounts by children. The potential for long-term oral toxicity is also low. Prolonged contact with propylene glycol is essentially non-irritating to the skin. Undiluted propylene glycol is minimally irritating to the eye, and can produce a slight, temporary inflammation of the conjunctiva. Exposure to mists may cause irritation of both the eye and the upper airway. Inhalation of propylene glycol vapours may be irritating to some individuals. It is therefore recommended that propylene glycol not be used in applications where inhalation exposure or human eye contact with the spray mists of these materials is likely, such as fogs for theatrical productions or antifreeze solutions for emergency eye wash stations. Propylene glycol show s no evidence of causing cancer or genetic toxicity. Research has suggested that individuals who cannot tolerate propylene glycol probably experience a special form of irritation, but they only rarely develop allergic contact dermatitis. Other investigators believe that the incidence of allergic contact dermatitis in people exposed to propylene glycol may be greater than 2% in patients with eczema. One study strongly suggests a connection of the concentrations of propylene glycol in houses and development of asthma and allergic reactions, such as inflammation of the cose and hives, in children, including asthma, hay fever, eczema and allergies, with increased risk of developing numerous respiratory and immune disorders in children, including asthma, hay fever, eczema and allergies, with increased risk ranging from 50% to 180%.

	Patients with bladder inflammation and vulvodynia (chronic pain of the vulva) may be especially sensitive to propylene glycol. Women suffering with yeast infections may notice that some over the counter creams cause intense burning. Post-menopausal women who require the use of an oestrogen cream may notice that creams made with propylene glycol often cause extremely uncomfortable burning along the vulva and around the anus. Some electronic cigarette users who inhale propylene glycol vapour may experience dryness of the throat or shortness of breath. Adverse responses to administration of drugs which use propylene glycol as an incipient have been seen in a number of people especially at high doses. These include low blood pressure, slow heart rate, ECG abnormalities, heartbeat irregularities, lactic acidosis, breakdown of red cells and cardiac arrest.		
DODECYLBENZENESULFONIC ACID	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. Linear alkyl benzene sulfonates are derived from strong corrosive acids. Animal testing has shown they can cause skin reactions, eye irritation, sluggishness, passage of frequent watery stools, weakness and may lead to death. They may also react with surfaces of the mouth and intestines, depending on the concentration exposed to. There is no evidence of harm to the unborn baby or tendency to cause cancer. ADI: 2.5 mg/kg/day NOEL: 250 mg/kg/day		
BENZALKONIUM CHLORIDE & DIDECYLDIMETHYLAMMONIUM CHLORIDE & SODIUM METASILICATE, ANHYDROUS & DODECYLBENZENESULFONIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.		
BENZALKONIUM CHLORIDE & DODECYLBENZENESULFONIC ACID	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there).		
ETHYLENE GLYCOL MONOBUTYL ETHER & PROPYLENE GLYCOL & DODECYLBENZENESULFONIC ACID	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
DIDECYLDIMETHYLAMMONIUM CHLORIDE & SODIUM METASILICATE, ANHYDROUS	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	×

Legend: 🔰

Data either not available or does not fill the criteria for classification
 Data available to make classification

## **SECTION 12 Ecological information**

Multi Kleen Degreaser & Covid-19 Killer Concentrate	Endpoint	Test Duration (hr)		Species		Value	Source
	Not Available	Not Available		Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)		Species		Value	Source
benzalkonium chloride	NOEC(ECx)	48h		Crustacea		0.3mg/l	4
	EC50	96h		Algae or other aquatic plants		<0.96mg/L	4
ethylene glycol monobutyl ether	Endpoint	Test Duration (hr)		Species		Value	Source
	LC50	96h		Fish		1250mg/l	2
	EC50	72h		Algae or other aquatic plants		623mg/l	2
	EC50	48h		Crustacea		164mg/l	2
	EC10(ECx)	48h		Crustacea		7.2mg/l	2
	EC50	96h		Algae or other aquatic plants		720mg/l	2
	Endpoint	Test Duration (hr)	S	pecies	Valu	ıe	Source
	EC50(ECx)	96h	A	lgae or other aquatic plants	0.00	8-0.024mg/L	4
didecyldimethylammonium chloride	LC50	96h	F	ish	0.16	6-0.27mg/L	4
chionae	EC50	48h	С	rustacea	0.01	4-0.022mg/L	4
	EC50	96h	A	lgae or other aquatic plants	0.00	08-0.024mg/L	4
sodium metasilicate, anhydrous	Endpoint	Test Duration (hr)	S	Species	Val	ue	Source
	EC50(ECx)	48h	C	Crustacea	22.	94-49.01mg/l	4

	EC50	72h	Algae or other aquatic plants	207mg/l	2
	LC50	96h	Fish	180mg/l	1
	EC50	48h	Crustacea	22.94-49.01mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	336h	Algae or other aquatic plants	<5300mg/l	1
	EC50	72h	Algae or other aquatic plants	19300mg/l	2
propylene glycol	LC50	96h	Fish	>10000mg/l	2
	EC50	48h	Crustacea	>114.4mg/L	4
	EC50	96h	Algae or other aquatic plants	19000mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	21mg/l	2
	LC50	96h	Fish	1.67mg/l	2
dodecylbenzenesulfonic acid	EC50	48h	Crustacea	2.5mg/l	2
	NOEC(ECx)	720h	Crustacea	0.046mg/l	2
	EC50	96h	Algae or other aquatic plants	12.086mg/l	2
Legend:	V3.12 (QSAR) -	Aquatic Toxicity Data (Estimated) 4.	HA Registered Substances - Ecotoxicological Inform. US EPA, Ecotox database - Aquatic Toxicity Data 5. I 1 (Japan) - Bioconcentration Data 8. Vendor Data		

Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

Toxic to aquatic organisms.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol monobutyl ether	LOW (Half-life = 56 days)	LOW (Half-life = 1.37 days)
propylene glycol	LOW	LOW
dodecylbenzenesulfonic acid	HIGH	HIGH

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
ethylene glycol monobutyl ether	LOW (BCF = 2.51)
propylene glycol	LOW (BCF = 1)
dodecylbenzenesulfonic acid	LOW (BCF = 140)

#### Mobility in soil

Ingredient	Mobility
ethylene glycol monobutyl ether	HIGH (KOC = 1)
propylene glycol	HIGH (KOC = 1)
dodecylbenzenesulfonic acid	LOW (KOC = 16830)

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal	<ul> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> <li>Otherwise: <ul> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sever may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> </li> </ul>

## **SECTION 14 Transport information**

	8
Marine Pollutant	NO
HAZCHEM	2X

#### Land transport (ADG)

UN number	1760			
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains benzalkonium chloride and didecyldimethylammonium chloride)			
Transport hazard class(es)	Class     8       Subrisk     Not Applicable			
Packing group	III			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions223 274Limited quantity5 L			

## Air transport (ICAO-IATA / DGR)

UN number	1760			
UN proper shipping name	Corrosive liquid, n.o.s. * (contains benzalkonium chloride and didecyldimethylammonium chloride)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L		
Packing group	III			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions         Cargo Only Packing Instructions         Cargo Only Maximum Qty / Pack         Passenger and Cargo Packing Instructions         Passenger and Cargo Maximum Qty / Pack         Passenger and Cargo Limited Quantity Packing Instructions         Passenger and Cargo Limited Maximum Qty / Pack		A3 A803 856 60 L 852 5 L Y841 1 L	

#### Sea transport (IMDG-Code / GGVSee)

UN number	1760		
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains benzalkonium chloride and didecyldimethylammonium chloride)		
Transport hazard class(es)	IMDG Class     8       IMDG Subrisk     Not Applicable		
Packing group	11		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-A , S-BSpecial provisions223 274Limited Quantities5 L		

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
benzalkonium chloride	Not Available
ethylene glycol monobutyl ether	Not Available
didecyldimethylammonium chloride	Not Available
sodium metasilicate, anhydrous	Not Available
propylene glycol	Not Available
dodecylbenzenesulfonic acid	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
benzalkonium chloride	Not Available
ethylene glycol monobutyl ether	Not Available
didecyldimethylammonium chloride	Not Available
sodium metasilicate, anhydrous	Not Available
propylene glycol	Not Available
dodecylbenzenesulfonic acid	Not Available

## **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

l	benzalkonium chloride is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	
	Schedule 5	Australian Inventory of Industrial Chemicals (AIIC)	
l	ethylene glycol monobutyl ether is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule $6$	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	
l	didecyldimethylammonium chloride is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	Schedule 6	
Schedule 5		Australian Inventory of Industrial Chemicals (AIIC)	
l	sodium metasilicate, anhydrous is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)	
l	propylene glycol is found on the following regulatory lists		
	Australian Inventory of Industrial Chemicals (AIIC)		
l	dodecylbenzenesulfonic acid is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)	

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (benzalkonium chloride; ethylene glycol monobutyl ether; didecyldimethylammonium chloride; sodium metasilicate, anhydrous; propylene glycol; dodecylbenzenesulfonic acid)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (benzalkonium chloride)
Japan - ENCS	No (benzalkonium chloride)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	No (benzalkonium chloride)
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	19/07/2021
Initial Date	29/06/2021

#### SDS Version Summary

Version	Date of Update	Sections Updated
3.1	30/06/2021	Acute Health (eye), Acute Health (swallowed), Chronic Health, Classification, Environmental, Ingredients, Storage (storage incompatibility), Use

Version	Date of Update	Sections Updated
4.1	19/07/2021	Ingredients, Synonyms, Use, Name

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

